



APart

PM7400MKII



Description

This stereo pre-amplifier is very easy-to-use. It is provided with 6 line inputs and 2 microphone inputs. Microphone and line inputs have a separate three-band tone control. Both microphones have an individual volume control. The 6 line inputs have a general volume control. Further the PM7400MKII is equipped with 2 stereo output zones with individual master volume control.

The PM7400MKII has a voice-activated mixing with micro (VOX). The external priority on micro 1 mutes the music.

Only Hi-Q components are used in a Low Noise design.

Everything has been built-in in a 19" 1 unit housing without fan.

NOTE: for rack mounting we advise you to use the PA-19 support.

Technical Specifications

Inputs:	Line 1	XLR Balanced 0dB, 20kOhm
	Line 2-3-4-5-6	RCA Cinch, 500 mV 10 kOhm
	Mic 1-2	Balanced: - Jack front - Combo rear -50dB/600 Ohm
Outputs:	Zone1:	RCA cinch 0dB/600 Ohm
	Zone 2:	XLR Balanced 0dB / 100 Ohm Hi-Quality balanced driver circuit
Frequency response:		20 Hz - 25 kHz
Distortion:		<0.01%
Dimensions (H x W x D):		44 x 483 x 275 mm
Weight:		2 Kg