
MB 88 U Dual - dynamic USB/XLR mic




Caution!

EΝ

- Special two-way microphone, USB and XLR both workable Compatible with any computer based DAW The extremely detailed sound reproduction makes it ideal for recording vocals, acoustic instruments and just about any other sound source High quality A/D convertor with 16 bit, 48 kHz sampling rate Solid die-cast construction
 - and put it in its case. Clean with damp cloth only.





Connection / Supply XLR / USB Transducer concept dynamic Directivity Cardioid Field sensitivity [mV/ Pa] 2.1 Field sensitivity [dB re 1V/ Pa] -53.8 Equivalent noise level [dB(A)] 13.3 Signal-to-noise ratio [dB(A)] 80.7 Maximum SPL [dB SPL @ 1% THD] 137 Electric impedance [ohm @ 1 kHz] 600 20 - 16.000 Hz Frequency response 0.1 m -10 dB Weight 236 q

For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of. Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.

This product is subject to the European Waste Electrical and Electronic Equipment Directive (WEEE) in its currently valid version. Do not dispose of your old device with your normal household waste. Dispose of this product through an approved waste disposal firm or through your local waste facility. Comply with the rules and regulations that apply in your country. If in doubt, consult your local waste disposal facility.

